

Email: sales@saheatpump.co.za

Tel: 011 394 7071

Fax: 011 394 1319

Dimension (Measure: mm)

SIZE	SHPI 200E	SHPI 250E	SHPI 300E
A	1650	1535	1840
B	1185	1070	1280
C	1025	910	1120
D	Ø560	Ø640	Ø640
E	Ø50	450	450
F	250	250	250
G	32.5	32.5	32.5
M	1075	910	1120
N	1135	1020	1230
V	925	830	1020
P	40	40	40

Residential Integrated Units:

- Fully integrated unit makes the use of a separate geyser obsolete.
- Manufactured from high quality 316L stainless steel for increased product life span
- 60°C hot water
- Vertical installation uses less space
- No need for additional plumbing work between geyser and heat pump
- Low noise levels
- Auto Defrost
- Easy installation and integration with existing plumbing
- External heating coil
- SANS 151 Certified
- Qualifies for SANS 10400-XA
- Manually activated 3kw back up electrical element

Technical Specifications

Model		SHPI200E	SHPI250E	SHPI300E
Heating Capacity	kW	2.8	2.8	4
Water Tank Volume	L	175 L	225 L	275 L
Power Input	W	760	760	1430
Power Supply	V/Ph/Hz	220-230/1/50	220-230/1/50	220-230/1/50
Waterproof Factor		IPX4	IPX4	IPX4
Compressor		1	1	1
Rated Outlet Water	°C	55	55	55
Max.Outlet Water Temperature	°C	60	60	60
Air Volume	m3/h	450	450	450
Air Pressure	Pa	60	60	60
Duct Diameter	mm	Ø 150	Ø 150	Ø 150
Noise	dB(A)	49	49	49
Refrigerant		134a	134a	134a
Water Inlet / Outlet Size	inch	20 mm	20 mm	20 mm
Net Dimensions	mm	Ø560x1650	Ø640x1535	Ø640x1880
Package Dimensions	mm	625x625x1860	705x705x1750	705x705x1960
Net Weight	kg	81	84	95
Gross Weight	kg	99	106	106

